

LED EXIT LIGHT BOX (ตัวถังยาว 130 cm)
MTX SERIES



MTX-20R-1B



MTX-20R-1C

Mode of operation: Maintained

Input voltage: 220 - 240 Vac / 50 Hz (สายไฟออกทางด้านบนตัวเครื่อง)

Lamps: LM-80 certified mid-power/high-lumen LEDs

Color temperature: 6500 ± 500 K

Battery: Lithium iron phosphate (LiFePO₄)

IR Remote*: for Test, Dim and AutoTest Enable/Disable


Manual test: 90-min test by either pushing button or using remote control*

AutoTest: 90-min test every 4 weeks (Enable/Disable selectable)

Standards: TIS 1955-2551, ISO 9001:2015

Casing: 1.8-mm-thick extruded aluminum coated with powder paint

Installation schemes



*Remote control not included in the package
*รีโมทคอนโทรลเป็นอุปกรณ์เสริมซึ่งจะจำหน่ายแยกกับผลิตภัณฑ์

MTX-20R SERIES (พื้นที่อะคริลิค 277 มม. x 1277 มม.)

Model	Installation		Signage	Backup Time	Dimension	Remote Support
	Scheme	Figure				
MTX-20R-1B	ติดผนัง	B	Single sided	3 hours	1300 mm x 120 mm x 300 mm	Yes
MTX-20R-1C	แขวนลอย	C				