## WATERPROOF LED EMERGENCY LIGHT WITH LITHIUM IRON PHOSPHATE BATTERY PWD SERIES











## Specification

Mode of operation: Non-maintained

Input voltage: 220 - 240 Vac / 50 Hz (สายไฟ AC 3 ขา แบบมีกราวนด์)

Battery type: Lithium iron phosphate LiFePO<sub>4</sub> (UL, ISO 9001) Battery charging method: Constant voltage / current limit

with SMART-CHARGER™

Lamps: LM-80 certified mid-power/high-lumen LEDs on metal-core PCB

with high thermal conductive nylon

Color temperature: Warm white 3500 - 4000 K, CRI > 80

Brightness: 4 programmable brightness levels for extended backup times

**Manual test:** 90-min test by either pushing button or using remote control\*

AutoTest: 90-min test every 4 weeks (Enable/Disable selectable)

IR Remote\*: for ON, OFF, Test, Dim and AutoTest Enable/Disable

**Standards:** TIS 1955-2551, ISO 9001:2015

Casing: 1.7-mm-thick extruded aluminum coated with powder paint

Degree of protection: IP65

Operating temperature:  $10^{\circ}\text{C} \sim 40^{\circ}\text{C}$ 

\*Remote control not included in the package \*รีโมทคอนโทรลเป็นอุปกรณ์เสริมซึ่งจะจำหน่ายแยกกับผลิตภัณฑ์

Model	Initial Mode	Lamp Rated Power	Luminuous Flux @Level 4	Battery	Backup Time		Weight
					@Level 4	@Level 1	vveignt
PWD-IP65-12P4T	Standard	2 x 12 W	2 x 600 lm	3.2 V 12000 mAH	4 hrs	12 hrs	0.82 kg